

## NEW 20 lb. BAG

TimberFill is now available in a 20 lb bag—same great coverage per pound, now with easier handling and improved equipment compatibility.



### Attic Coverage Chart

**LOOSE-FILL ATTIC BLANKET APPLICATION** 20lb (9kg) Bag of TimberFill

R-Value at 75°F Mean Temp	Minimum Thickness (inches)		Net Coverage (no adjustment for framing)			Net Coverage (adjusted for 2x6" framing on 16" centers)	
	Initial Installed Thickness	Settled Thickness	Maximum Sq. Ft. per Bag	Minimum Bags per 1,000 Sq. Ft.	Minimum Weight per Sq. Ft.	Maximum Sq. Ft. per Bag	Minimum Bags per 1,000 Sq. Ft.
11	3.8	3.4	54.1	18.5	0.37	59.6	16.8
13	4.4	4.0	45.5	22	0.44	50.2	19.9
19	6.3	5.7	30.3	33	0.66	33.3	30.1
22	7.3	6.6	26.0	38.5	0.77	28.1	35.5
24	8.0	7.2	23.5	42.5	0.85	25.4	39.4
26	8.6	7.8	21.7	46	0.92	23.3	43.0
30	9.9	8.9	18.7	53.5	1.07	19.8	50.5
32	10.6	9.5	17.4	57.5	1.15	18.4	54.3
38	12.5	11.3	14.6	68.5	1.37	15.2	65.6
40	13.2	11.9	13.9	72	1.44	14.5	68.8
45	14.8	13.4	12.3	81.5	1.63	12.8	77.9
48	15.8	14.2	11.5	87	1.74	11.9	84.1
49	16.1	14.5	11.2	89	1.78	11.6	86.0
50	16.5	14.8	11.0	91	1.82	11.4	87.8
55	18.1	16.3	10	100	2.00	10.3	96.9
60	19.7	17.8	9.1	109.5	2.19	9.5	105.8
70	23.0	20.7	7.8	128	2.56	8.0	125.4

Installed attic thicknesses for this chart were determined according to ASTM C1374. Please use for estimating purposes only. Jobsite conditions, application method, equipment, settings, and hose length can influence coverage.



### Sidewall and Floor Coverage Chart

**DRY DENSE-PACK SIDEWALL & FLOOR APPLICATION**  
20 lb (9kg) bag of TimberFill (3.5 pcf minimum installed density)

Framing	Thermal Resistance (R-Value)	Installed Thickness (Inches)	Minimum Wt Per Sq. Ft. lb/ft2	Maximum Coverage per Bag (Adjusted for Framing)	
				16" o.c. ft2/Bag	24" o.c. ft2/Bag
2x4	13	3.5	1.02	22.7	21.6
2x6	21	5.5	1.60	14.4	13.8
2x8	28	7.25	2.11	11.0	10.5
2x10	35	9.25	2.70	8.6	8.2

This document is applicable in conjunction with other TimberHP documentation. Please heed our detailed application notes in your application. National building regulations must be complied with. Information on and suitability of the material for the intended purpose must in each case be examined by the customer. TimberHP® accepts no liability. This also applies to printing errors and subsequent amendments to technical data. REV 07-2025

Environmental conditions, application and technique will influence coverage and as actual results may vary, coverage is not guaranteed by the manufacturer. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Per our SDS, keep a clean jobsite and use mechanical ventilation to minimize dust levels during application. Use safety eyewear and a NIOSH-approved N95 particulate respirator. This product does not contain asbestos, fiberglass or formaldehyde in its manufacturing process. This coverage chart was produced using a Volumatic III blowing machine at Air = 2.0 PSI (end of hose), Gate = 8, 3rd Gear. Additional safety information and installation instructions can be found at [www.timberhp.com/TimberFill](http://www.timberhp.com/TimberFill)



### ATTIC CARD

# TIMBERFILL®

by TimberHP

This insulation has been installed in conformance with the above recommendations, to provide a value of R-\_\_\_\_\_ using \_\_\_\_\_ 20 lb. bags of this insulation to cover \_\_\_\_\_ square feet of area.

Builder's Signature: \_\_\_\_\_

Company Name: \_\_\_\_\_

Date: \_\_\_\_\_

Applicator's Signature: \_\_\_\_\_

Company Name: \_\_\_\_\_

Date: \_\_\_\_\_

MANUFACTURED BY  
TimberHP  
1 Main St / PO Box 119  
Madison, Maine 04950

[www.timberhp.com](http://www.timberhp.com)  
toll free 1-855-755-1359



TimberHP™ is a registered trademark.  
© 2025 TimberHP  
All rights reserved.

**TIMBERFILL®**  
by TimberHP



TimberHP™ is a registered trademark.  
© 2025 TimberHP  
All rights reserved.