

COVERAGE CHART FOR 25 lb. BAG

This chart corresponds to TimberFill's 25 lb bag, which was discontinued on July 14, 2025. Please confirm bag weight before use and refer to the correct coverage chart for the 20 lb bag if applicable.

TimberFill
by TimberHP



LOOSE-FILL ATTIC BLANKET APPLICATION 25lbs (11.3kg) - TimberFill							
R-Value at 75°F Mean Temp	Minimum Thickness (inches)		Net Coverage (no adjustment for framing)			Net Coverage (adjusted for 2x6" framing on 16" centers)	
	Initial Installed Thickness	Settled Thickness	Maximum Sq. Ft. per Bag	Minimum Bags per 1,000 Sq. Ft.	Minimum Weight per Sq. Ft.	Maximum Sq. Ft. per Bag	Minimum Bags per 1,000 Sq. Ft.
11	3.8	3.4	67.8	14.8	0.37	74.8	13.4
13	4.4	4.0	56.5	17.7	0.44	62.4	16.0
19	6.3	5.7	37.7	26.6	0.66	41.4	24.2
22	7.3	6.6	32.3	31.0	0.77	35.0	28.6
24	8.0	7.2	29.4	34.0	0.85	31.7	31.5
26	8.6	7.8	27.1	36.9	0.92	29.0	34.5
30	9.9	8.9	23.3	42.9	1.07	24.7	40.4
32	10.6	9.5	21.8	45.9	1.15	23.1	43.4
38	12.5	11.3	18.3	54.8	1.37	19.1	52.3
40	13.2	11.9	17.3	57.8	1.44	18.1	55.3
45	14.8	13.4	15.3	65.2	1.63	16.0	62.7
48	15.8	14.2	14.4	69.7	1.74	14.9	67.1
49	16.1	14.5	14.1	71.2	1.78	14.6	68.6
50	16.5	14.8	13.8	72.6	1.82	14.3	70.1
55	18.1	16.3	12.5	80.1	2.00	12.9	77.6
60	19.7	17.8	11.4	87.5	2.19	11.8	85.0
70	23.0	20.7	9.8	102.4	2.56	10.0	99.9

Installed attic thicknesses for this chart were determined according to ASTM C1374. Please use for estimating purposes only. Jobsite conditions, application method, equipment, settings, and hose length can influence coverage.



DRY DENSE-PACK SIDEWALL & FLOOR APPLICATION 25 lbs (11.3kg) - TimberFill (3.0 pcf minimum installed density)					
Framing	Thermal Resistance (R-Value)	Installed Thickness (Inches)	Minimum Wt Per Sq. Ft. lb/ft2	Maximum Coverage per Bag (Adjusted for Framing)	
				16" o.c. ft2/Bag	24" o.c. ft2/Bag
2x4	13	3.5	0.88	32.9	31.4
2x6	21	5.5	1.38	20.9	20.0
2x8	28	7.25	1.81	15.9	15.2
2x10	35	9.25	2.31	12.4	11.9

Environmental conditions, application and technique will influence coverage and as actual results may vary, coverage is not guaranteed by the manufacturer. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Per our SDS, keep a clean jobsite and use mechanical ventilation to minimize dust levels during application. Use safety eyewear and a NIOSH-approved N95 particulate respirator. This product does not contain asbestos, fiberglass or formaldehyde in its manufacturing process. This coverage chart was produced using a Volumatic III blowing machine at Air = 2.0 PSI (end of hose), Gate = 8, 3rd Gear. Additional safety information and installation instructions can be found at www.timberhp.com/TimberFill



This document is applicable in conjunction with other TimberHP documentation. Please heed our detailed application notes in your application. National building regulations must be complied with. Information on and suitability of the material for the intended purpose must in each case be examined by the customer. TimberHP® accepts no liability. This also applies to printing errors and subsequent amendments to technical data. REV 07-2025



ATTIC CARD

TimberFill

by TimberHP

This insulation has been installed in conformance with the above recommendations, to provide a value of R- _____ using _____ 25 lb. bags of this insulation to cover _____ square feet of area.

Builder's Signature: _____

Company Name: _____

Date: _____

Applicator's Signature: _____

Company Name: _____

Date: _____

MANUFACTURED BY

TimberHP

1 Main St / PO Box 119

Madison, Maine 04950

www.timberhp.com

toll free 1-855-755-1359



TimberHP™ is a registered trademark.
© 2025 TimberHP
All rights reserved.